

## TOWCASTERS

Flexello Towcasters are provided in sets of four heavy-duty fabricated casters and are available in sizes of 10" and 12" with load capacities of 22,000 lbs. and 26,400 lbs. per set respectively. The Flexello Towcaster system is designed to move ISO freight containers quickly and easily without the use of expensive equipment such as cranes, gantries, or side-loading forklifts.

The Flexello Towcaster system includes two swivel and two fixed casters featuring adapter plates that lock positively (via quick-action securing screws) into the corner castings incorporated into all ISO freight containers. A special lifting handle and ratchet spanner, included in the set, facilitate easy lifting and locking. Spare parts for Towcaster are available on request.

Available optionally in sets of two, the patented Flexello Towbar enables towing by tractor, fork truck or other towing vehicle. It measures 8 feet long and fits easily and securely into the ISO container corner brackets immediately above the swivel Towcasters. The Towbars attach to the towing vehicle using standard link pins up to 1-1/2" diameter (not supplied).

TOWCASTER	SET #1	SET #2
Wheel Diameter	10"	12"
Tread Width	3"	4"
Mounting Height	15-3/4"	17-7/8"
Load Capacity	22,000 lbs.	26,400 lbs.
Wheel Type	Polyurethane on Cast Iron	Polyurethane on Cast Iron
Part #	ISO-210SUTM	ISO-312SUTM



Towcaster Locking Screws, Lifting Handle, Ratchet Spanner and the optional Towbar.



Swivel Towcaster



Fixed Towcaster

## UTP SERIES

The Flexello UTP Series is a combination twin-wheel swivel caster and leveling foot. It features an adjustable stem and foot for leveling that is concentric with the caster spindle. The body is constructed of high-impact nylon for strength and appearance. The stem is made of sturdy carbon steel. The UTP Series caster is ideal for appliance cabinets, medical carts and furniture, racks, displays, and other heavy equipment requiring period rolling and level, stationary positioning. The UTP Series caster is available in standard black and custom colors. Other options include a top plate design, foot brake, and directional lock.

### UTP SERIES

Wheel Diameter	2-5/8"
Minimum Height*	4-15/16"
Maximum Height**	5-1/2"
Height Adjustment	9/16"
Foot Diameter	1-1/8"
Swivel Radius	2-1/8"
Overall Width	2-7/8"
Tread Width	11/16"
Load Capacity	330 lbs.
Bearing	Ball Raceway
Wheel Type	Nylon 6
Swivel Part #	UTP-066BNOP

\* Minimum clearance of 3/8" between the foot and floor when the stem is raised for rolling.

\*\* Maximum clearance 9/16" between the wheel and floor when the stem is lowered for leveling.



UTP Series - Adjustable Stem & Foot