

PL SERIES - Polypropylene Wheels


Wheel Type: Polypropylene
 Standard Finish: Black
 Temperature Range: Normal room temperature

- Wheel Characteristics:**
- Economical alternative to Nylon wheels
 - Preferred for use on good floor surfaces to carry light loads at room temperature
 - Resistant to most chemicals and acids
 - Non-marking, non-chipping, and steam-cleanable
 - Available with Delrin bearings



A = Wheel Diameter B = Tread Width C = Hub Length D = Bore

| PL SERIES | | | | | | | | |
|-----------|--------|--------|------|---------------|--------------|--------------|--------------|-----------------------|
| A | B | C | D | Load Capacity | Bearing Type | Wheel Weight | Wheel Part # | Used in Caster Series |
| 4" | 1-1/2" | 1-5/8" | 1/2" | 400 | Plain | .26 | 100 PL04 | 4, E |
| 4" | 2" | 2-3/8" | 3/4" | 450 | Roller | .34 | 100 PL1G | G, H, K |
| 5" | 1-1/2" | 1-5/8" | 1/2" | 450 | Plain | .36 | 125 PL04 | 4, E |
| 5" | 1-1/2" | 1-5/8" | 1/2" | 450 | Roller | .40 | 125 PL14 | 4, E |
| 5" | 2" | 2-3/8" | 3/4" | 650 | Roller | .46 | 125 PL1G | G, H, K |
| 6" | 2" | 2-3/8" | 3/4" | 750 | Roller | .52 | 150 PL1G | 5, G, H, K |
| 8" | 2" | 2-3/8" | 3/4" | 1000 | Roller | .73 | 200 PL1G | 5, G, H, K |



RP SERIES - Phenolic Resin Wheels

Wheel Type: "Revvoplast" Phenolic Resin
 Standard Finish: Black
 Temperature Range: -50°F to 260°F (For temperatures above 180°F, specify metal washers)
 Durometer: 90° Shore D; 02 Rockwell E

- Wheel Characteristics:**
- Manufactured from canvas duck reinforced phenolic resin
 - Extremely hard and will support high-static loadings for long periods
 - Low rolling resistance, hard wearing, shock resistant, and easy on floor surfaces
 - High resistance to chemical attack
 - Withstands high temperatures
 - Consult factory for high-temperature and laminated phenolic wheels



A = Wheel Diameter B = Tread Width C = Hub Length D = Bore

| RP SERIES | | | | | | | | |
|-----------|--------|----------|------|---------------|--------------|--------------|--------------|-----------------------|
| A | B | C | D | Load Capacity | Bearing Type | Wheel Weight | Wheel Part # | Used in Caster Series |
| 3" | 1-1/2" | 1-5/8" | 1/2" | 375 | Plain | .30 | 075 RP04 | 4 |
| 3" | 1-1/2" | 1-13/16" | 3/4" | 400 | Roller | .43 | 075 RP14 | 4 |
| 4" | 1-1/2" | 1-5/8" | 1/2" | 600 | Plain | .50 | 100 RP04 | E, 4 |
| 4" | 1-1/2" | 1-13/16" | 3/4" | 400 | Roller | .70 | 100 RP14 | E, 4 |
| 4" | 2" | 2-3/8" | 3/4" | 800 | Roller | .81 | 100 RP1G | G, H, K |
| 5" | 1-1/2" | 1-5/8" | 1/2" | 600 | Plain | .71 | 125 RP04 | E, 4 |
| 5" | 1-1/2" | 1-13/16" | 3/4" | 600 | Roller | .81 | 125 RP14 | E, 4 |
| 5" | 2" | 2-3/8" | 3/4" | 1000 | Roller | .92 | 125 RP1G | G, H, K |
| 6" | 2" | 2-3/8" | 3/4" | 1200 | Roller | .99 | 150 RP1G | 5, G, H, K |
| 8" | 2" | 2-3/8" | 3/4" | 1400 | Roller | 1.07 | 200 RP1G | 5, G, H, K |

